

PATENT SPECIFICATION

(11) 1 321 199

1 321 199

DRAWINGS ATTACHED

(21) Application No. 14482/71 (22) Filed 12 May 1971

(44) Complete Specification published 20 June 1973

(51) International Classification F16K 7/04//F16L 11/08

(52) Index at acceptance

F2V B1L1 B1L2

F2G 14C 29 2A 6P

F2P 1A10 1A28A 1A9 1B7

(72) Inventor LAWRENCE DONALD ALEXANDER JACKSON



(54) SLEEVE FOR A PINCH VALVE

(71) We, LAWJACK EQUIPMENT LIMITED, a Canadian Corporation, of 1975 Bois Franc Road, Montreal 382, Quebec, Canada, do hereby declare the invention for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to sleeves for pinch valves. Pinch valves have a resilient sleeve having a longitudinal bore defining a fluid flow path. The valve is closed by deforming opposite side walls of the bore into contact substantially to close the fluid flow path. The deformation may be caused by applying fluid pressure to the exterior wall of the sleeve or by squeezing the sleeve between upper and lower anvils by mechanical action.

The ends of the sleeve are normally held in spaced-apart positions, for example, by having integral flanges on the sleeve which are bolted to flanges on the ends of pipe lines. When the valve is closed the sleeve must accommodate the increased length of the body of the sleeve between the flanges caused by curvature of the sleeve. This causes strain in fabric reinforcing layers of the sleeve and leads to a short working life of the sleeve.

When pinch valves are used in a partly open condition in order to reduce or throttle the flow of fluid through the line to which they are connected, the sleeve tends to take the shape of a Venturi. The result is that a vacuum develops on the downstream side of the pinch. This vacuum is unstable and the internal pressure variations induce a flexing in the valve sleeve, which can cause early destruction to the valve sleeve, and in addition the fluttering produced in the sleeve by the Venturi effect can lead to severe vibration in the entire piping system. The existence of this phenomenon has made it necessary to put severe limits on the throttling range in which pinch valves can be safely employed.

The basic solution to the problem of fluttering of valve sleeves under partly

closed or throttling conditions, is to produce a sleeve which is sufficiently stiff so that it will not tend to collapse under the vacuum effect, and will thus maintain a stable shape.

According to the present invention there is provided a sleeve for a pinch valve comprising a tubular body member having an elastomeric inner wall defining a smooth flow path of substantially constant cross-section, and circumferential fabric reinforcing layers surrounding the inner wall and extending over the whole length of the body member between its ends, the middle portion of the body member being adapted to be deformed inwardly in order substantially to close the said flow path, and the body member having two circumferential regions respectively between its ends and the said middle portion in which the outer diameter is increased in order to stiffen the said regions of the sleeve and thereby enable them to resist inward deformation.

The end portions of the said circumferential fabric layers may be folded to form end flanges around the said inner wall. The flanges may be covered by a layer of elastomeric material and each flange may have an inner metal core.

The circumferential regions of increased outer diameter may be built up of layers of fabric and each end of each region may be tapered down to the diameter of the adjacent part of the body member. The outer surface of the sleeve may be covered by a layer of elastomeric material.

By the provision of two separate regions of increased diameter, respectively located adjacent the end portions of the pinch sleeve, extra stiffness is afforded to the sleeve on the downstream side of the pinch, irrespective of the direction of flow through the valve.

The invention will be described, by way of example, with reference to a preferred embodiment illustrated in the accompanying drawings, in which:—

Figure 1 is a longitudinal view, partly in section of a pinch valve sleeve according to the present invention;

Figure 2 is a transverse section taken on the line 2—2 of Figure 1;

Figure 3 is a partial longitudinal section taken from Figure 1 but showing a modified form of the reinforcements.

In the embodiment of the invention here shown for illustrative purposes the sleeve 1 is shown having a body member 2 and end flanges 3 and 4.

Means, now shown, are provided in the pinch valve assembly for applying pressure to the middle portion of the body member. This means may include a jacket surrounding the sleeve, into which pressurized fluid may be introduced for the purpose of compressing the sleeve to reduce the flow of fluid therethrough. Alternatively, the sleeve may be compressed by anvil means shown diagrammatically at 5 and 6 in Figure 1.

The body member 2 is cylindrical and has an inner wall 7 of non-corrosive elastomeric material to provide a smooth flow path of substantially constant cross-section through the body member.

The body member 2 is reinforced by a plurality of layers 8 of fabric which are wrapped circumferentially about the inner wall 7. In addition the body member 2 is circumferentially reinforced with additional material to increase its outer diameter at two regions A and B, one region A of reinforcement being located adjacent but spaced from the end flange 3, while the other region B or reinforcement is located adjacent but spaced from the end flange 4.

Each end of each of the circumferentially reinforced regions A and B is tapered down to the diameter of the adjacent part of the body member. The increased outer diameter of the regions A and B, and the tapers consist of layers 9 of fabric of successively decreasing width which are preferably placed between inner and outer layers 8a and 8b of the layers of fabric 8, in the manner shown in Figure 2.

The outer surface of the body member 2 is covered by a layer of an elastomeric material 10 which extends longitudinally over the middle portion of the sleeve and over the enlarged and reinforced regions A and B and, if desired, may extend as far as the end flanges 3 and 4.

The end portions of the layers 8 of the reinforcing fabric may be wrapped about metal end rings 12 and sealed by a layer of elastomeric material to form the end flanges 3 and 4. Alternatively the end portions of the layers 8 of the reinforcing fabric may be formed into a flange shape without metal end rings.

In the modification shown in Fig. 3 of the drawings an annular layer 11 of an elastomeric material is shown wrapped about the outer surface of the inner wall 7 to

form the base of the enlarged and reinforced regions A and B.

In using the sleeve, and upon closure of the valve, whether by the application of external pressurized fluid or by means of anvils 5 and 6, pressure is applied to the middle portion of the sleeve between the enlarged and reinforced regions A and B to bring the opposed walls of the flow path together.

This application of pressure and deformation causes the opposed walls of the sleeve to curve and to have increased length. By providing increased fabric length, such as by the sections of layers 8a and 8b incorporated in the enlarged and reinforced regions A and B, the fabric layers 8 in that section of the sleeve between the regions A and B do not have to stretch appreciably to accommodate the increased length of the sleeve. Rather, as the inner wall 7 stretches, the portions of the fabric layers 8a and 8b having a radial directional component in the regions A and B provide the required increased fabric length. Thus, there is less strain on the fabric layers as a whole, leading to longer life of the sleeve.

On opening of the valve the additional fabric material within the regions A and B will tend to return to their original position, assisted by the inner annular ring 11 of elastomeric material, and the outer surface of elastomeric material 10.

The reinforced and enlarged regions A and B effectively reinforce the sleeve in the areas between the end flanges 3 and 4 and the middle section of the sleeve where force is applied to close the valve, yet have sufficient elasticity built into them to ensure that the sleeve will, throughout its whole length, return to its normal configuration on the release of the closing pressure.

The enlarged and reinforced regions A and B sufficiently stiffen the sleeve to prevent fluttering of the sleeve under partly closed or throttling conditions so as to prevent collapse of the sleeve under the vacuum effect. Such a sleeve will thus maintain a stable shape under all operating conditions.

This built-in strength and elasticity will ensure that the valve can be operated to open and close over a longer working life than has been possible in the past.

WHAT WE CLAIM IS:—

1. A sleeve for a pinch valve comprising a tubular body member having an elastomeric inner wall defining a smooth flow path of substantially constant cross-section, and circumferential fabric reinforcing layers surrounding the inner wall and extending over the whole length of the body member between its ends, the middle portion of the body member being adapted to be deformed inwardly in order substantially to close the

- said flow path, and the body member having two circumferential regions respectively between its ends and the said middle portion in which the outer diameter is increased in order to stiffen the said regions of the sleeve and thereby enable them to resist inward deformation.
- 5 2. A pinch valve sleeve according to claim 1 in which the end portions of the said circumferential fabric layers are folded to form end flanges around the said inner wall.
- 10 3. A pinch valve sleeve according to claim 2 in which the said end flanges are covered by a layer of elastomeric material.
- 15 4. A pinch valve sleeve according to claim 2 or 3 in which the said end flanges have an inner metal core.
- 20 5. A pinch valve sleeve according to any preceding claim in which each end of each region of increased outer diameter is tapered down to the diameter of the adjacent part of the body member.
- 25 6. A pinch valve sleeve according to claim 5 in which the said regions of increased diameter are formed by layers of fabric of successively decreasing width interposed between layers of the fabric reinforcement.
- 30 7. A pinch valve sleeve according to claim 5 in which the said regions of increased diameter are each formed by a layer of elastomeric material wrapped around the said elastomeric inner wall and layers of fabric of successively decreasing width interposed between layers of the fabric reinforcement.
8. A pinch valve sleeve according to claim 1 in which the said fabric reinforcing layers have a greater length than the distance between the ends of the said inner wall.
9. A pinch valve sleeve according to claim 7 in which, when the valve is closed, some of the layers of reinforcing fabric adjacent the said inner wall are deformed radially to increase their length longitudinally of the sleeve by the said layer of elastomeric material, and the remaining outer layers of fabric of successively decreasing width are displaced radially by the layers of reinforcing fabric.
10. A pinch valve sleeve according to any preceding claim in which the outer surface of the sleeve is covered by a layer of elastomeric material.
11. A pinch valve sleeve substantially as described and shown in the accompanying drawings.
12. A pinch valve containing a pinch valve sleeve as claimed in any preceding claim.

BROMHEAD & CO.
Chartered Patent Agents,
Clifford's Inn,
Fetter Lane,
London, EC4A. 1NP.

FIG. 1




FIG. 2




FIG. 3

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US2004/031702

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16K7/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 259 985 A (BERGMANN WARREN C) 7 Apr11 1981 (1981-04-07) column 2, line 4 - column 4, line 53; figures 1-4	1,2
X	US 5 190 071 A (SULE AKOS) 2 March 1993 (1993-03-02) column 6, line 47 - column 8, line 61; figures 13-16	20
A	US 2003/097884 A1 (WHEELER MATTHEW G ET AL) 29 May 2003 (2003-05-29) figures 2-13	1,20,23
A	US 4 548 382 A (OTTING BILLY J) 22 October 1985 (1985-10-22) figures 1-8	1,20,23
	-/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

8 December 2004

Date of mailing of the international search report

17/12/2004

Name and mailing address of the ISA

European Patent Office, P.B. 6818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Heneghan, M

INTERNATIONAL SEARCH REPORT

Inter 1st Application No
PCT/US2004/031702

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 132 108 A (LEVITRONIX LLC) 12 September 2001 (2001-09-12) figures 1-6	1,20,23
A	US 2003/141470 A1 (IGARASHI HIROKI) 31 July 2003 (2003-07-31) figures 1-4	1,20,23
A	US 5 810 324 A (ERIKSSON PER-GOERAN ET AL) 22 September 1998 (1998-09-22) figures 1-7	1,20,23
A	US 6 036 166 A (OLSON DAVID L) 14 March 2000 (2000-03-14) figures 1-7	1,20,23
A	US 6 279 869 B1 (OLEWICZ TADEUSZ) 28 August 2001 (2001-08-28) figures 1-9c	1,20,23
A	US 2003/098069 A1 (PAWLAS GARY E ET AL) 29 May 2003 (2003-05-29) figures 2-11	1,20,23
A	US 5 379 790 A (BRUCE MARK L ET AL) 10 January 1995 (1995-01-10) figures 1-6	1,20,23

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US2004/031702

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4259985	A	07-04-1981	NONE	
US 5190071	A	02-03-1993	US 4496133 A US 4993456 A	29-01-1985 19-02-1991
US 2003097884	A1	29-05-2003	BR 0213503 A CA 2463035 A1 EP 1451657 A1 WO 03046675 A1	19-10-2004 05-06-2003 01-09-2004 05-06-2003
US 4548382	A	22-10-1985	NONE	
EP 1132108	A	12-09-2001	EP 1132108 A1 US 2001019117 A1	12-09-2001 06-09-2001
US 2003141470	A1	31-07-2003	JP 2001355748 A	26-12-2001
US 5810324	A	22-09-1998	EP 0841509 A1 JP 10089501 A	13-05-1998 10-04-1998
US 6036166	A	14-03-2000	NONE	
US 6279869	B1	28-08-2001	US 6494225 B1	17-12-2002
US 2003098069	A1	29-05-2003	BR 0214113 A CA 2464051 A1 EP 1451533 A1 WO 03046489 A1	13-10-2004 05-06-2003 01-09-2004 05-06-2003
US 5379790	A	10-01-1995	US 5316262 A	31-05-1994

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 03/09381

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 F16K7/04		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 F16K		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the International search (name of data base and, where practical, search terms used) EPO-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 379 790 A (BRUCE MARK L ET AL) 10 January 1995 (1995-01-10) column 3, line 59 -column 4, line 31; figures 5,6	1,4,6-12
X	US 6 036 166 A (OLSON DAVID L) 14 March 2000 (2000-03-14) column 1, line 51 -column 4, line 19; figures 1-6	1-4,12
X	US 2 674 435 A (ANGELL ROBERT C) 6 April 1954 (1954-04-06) column 2, line 19 -column 4, line 6; figures	1,4,5,12
A	GB 1 321 199 A (LAWJACK EQUIPMENT LTD) 20 June 1973 (1973-06-20) column 2, line 17 - line 58; figure 1	1-3,12
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the International filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the International filing date but later than the priority date claimed "T" later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the International search 21 July 2003		Date of mailing of the International search report 28/07/2003
Name and mailing address of the ISA European Patent Office, P.B. 5618 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Lane1, F-B

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 03/09381

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 6 279 869 B1 (OLEWICZ TADEUSZ) 28 August 2001 (2001-08-28) column 4, line 66 -column 6, line 14 column 12, line 63 -column 13, line 9; figures 1,2,12C</p>	1,6,12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 03/09381

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5379790	A	10-01-1995	US 5316262 A	31-05-1994
US 6036166	A	14-03-2000	NONE	
US 2674435	A	06-04-1954	NONE	
GB 1321199	A	20-06-1973	NONE	
US 6279869	B1	28-08-2001	US 6494225 B1	17-12-2002

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.